

# XFAM-022Z-CFV-081

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	33.1
Unit Length (in):	40.6
Unit Width (in):	17.2
Ship Weight (lbs):	226.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

## Electrical

Max Fuse Size:	35
Min Circuit Ampacity:	20.7
Compressor:	ZS15KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	68.0
Compressor LRA - Half winding:	
Compressor RLA:	15.7
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	09-Sep-2016	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	12138	Air Flow Rate (CFM)	2050

**90°F Ambient Air Temperature**

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
0	7,120	95.1	5.1	6.4
5	8,070	95.8	5.8	7.1
10	9,100	96.5	6.5	7.7
15	10,200	97.2	7.2	8.5
20	11,400	98.0	8.0	9.3
25	12,700	98.9	8.9	10.1