

XFAM-030Z-TFC-081

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	33.1
Unit Length (in):	40.6
Unit Width (in):	17.2
Ship Weight (lbs):	226.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/2 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	42

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	20.1
Compressor:	ZS21KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	93.0
Compressor LRA - Half winding:	
Compressor RLA:	15.2
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	09-Sep-2016	Return Gas Temp. (°F):	40
Compressor:	ZS21KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	12152	Air Flow Rate (CFM)	2050

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
0	10,700	97.3	7.3	7.2
5	12,100	98.2	8.2	7.9
10	13,600	99.2	9.2	8.6
15	15,200	100.3	10.3	9.4
20	17,000	101.4	11.4	10.2
25	18,900	102.6	12.6	11.1