

ZF06K4E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Low Temp, Liquid Injected

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Accessories

<u>Category</u>	<u>PartNumber</u>	<u>Description</u>
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
	018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
	018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
	018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
	018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
	018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
	018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
	018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
	018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
	918-0043-00	Crankcase Heater Kit, 240V, 70W, Wrap Around, 48" Lead Length
	918-0043-01	Crankcase Heater Kit, 480V, 70W, Wrap Around, 48" Lead Length
	918-0043-02	Crankcase Heater Kit, 575V, 70W, Wrap Around, 48" Lead Length
	918-0043-07	Crankcase Heater Kit, 120V, 70W, Wrap Around, 48" Lead Length
	998-7026-00	Crankcase Heater Enclosure Box
Discharge Line	998-0166-00	Topcap Thermistor Kit
	998-0540-00	Discharge Line Thermostat Kit, 1/2" DLT-Stat 12" Leads, 2-Wire
	998-0540-02	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads, 2-Wire
	998-0548-00	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads With Alarm
	998-7022-02	Discharge Line Thermostat Kit, 1/2", 36" Leads (Conduit Ready)
Electrical	085-0160-00	3 Phase Voltage Monitor. For use with all Copeland 3 Phase Compressors. Consult model family nomenclature for electrical definition in the model number.
Liquid Injection	505-0819-00	Valve Cap (When Injection is not used)

Matthew Meier

Page 1 of 2

03/28/2018

Category	PartNumber	Description
	998-0500-00	DTC Valve (Liquid Line 3/8" Sweat Tube, 193F Set Point) - liquid injection only applications
	998-0500-01	DTC Valve (Liquid Line 1/4" Flare, 193F Set Point) - liquid injection only applications
Miscellaneous	085-CP2M-7K	Dual High and Low Pressure Cut-Out Control
	998-E022-01	Polyol Ester Oil. Approved for use with specific Copeland Hermetic & Semi Hermetic models. Consult specific model family nomenclatures for oil identifier in the model number.
Mounting	527-0116-00	Spacer Mounting Kit, 30-35 Durometer, 1.45" OD, 0.44" ID, 0.75" Height
	527-0157-00	High Durometer Mount Kit, 60-70 Durometer, 1.62" OD, 0.44" ID, 1.16" Height
Mounting	998-0178-00	Hard Mount Kit, 1.87" OD, 0.69" ID, 0.31" Height
Oil Management	65365	Oil Management Control w/ Junction Box 24V, 50/60Hz
	65366	Oil Management Control w/ Series Relief Connector 24V, 50/60Hz
	65668	Oil Management, OMB Adapter (3/4" NPT)
	66650	Oil Management, OMB Adapter (1 1/4"-12 Rotalock)
Service Valves and	998-0034-01	Stub Tube to Rotalock, 3/4" Sweat to 1 1/4"-12 Thread
	998-0034-07	Rotalock to Stub Tube Adapter, 1 1/4"-12 Thread to 3/4" Sweat
	998-0034-15	Stub Tube to Rotalock, 1/2" Sweat (OD Applied) to 1"-14 Thread
	998-0034-18	Rotalock to Stub Tube Adapter, 1"-14 Thread to 1/2" Sweat
	998-0069-01	Stub Tube to Rotalock, 3/4" Sweat to 1 1/4"-12 Thread and 1/2" Sweat to 1"-14 Thread
	998-0510-98	Service Valve Kit, 1"-14 Thread to 1/2" Sweat
	998-0511-02	Service Valve Kit, 1 1/4"-12 Thread to 3/4" Sweat
	998-5100-42	Service Valve Kit, 1 1/4"-12 Thread to 3/4" Sweat and 1"-14 Thread to 1/2" Sweat