

ZS09KAE-TF5

HCFC, R-22, 60 Hz, 3- Phase, 200/230 V
High Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	20 / 120
RG(°F)/Liq(°F)	65.0 / 130.0	40.0 / 120.0
Capacity (Btu/hr)	14700	9520
Power (W):	1595	1275
Current (Amps):	4.80	4.05
EER (Btu/Wh):	9.20	7.45
Mass Flow (lbs/hr):	232	148
Sound Power (dBA):	70 Avg	75 Max
Vibration mils(peak-)	2.0 Avg	3.0 Max
Record Date:	2016-07-05	

Mechanical

Number of Cylinders:	0	Displacement(in ³ /Rev):	1.31
Bore Size(in):	0.00	Displacement(ft ³ /hr):	158.84
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	15.72	Mounting Height (in):	16.00 *
Suction Size (in),Type:	3/4 Stub		
Discharge Size (in),Type:	1/2 Stub		
Oil Recharge (oz):	19		
Initial Oil Charge (oz):	25		
Net Weight (lbs):	49		
Internal Free Volume (in ³):	128.0		
Horse Power:	1.3		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*(Amp):	55.4	MCC (Amps):	10.2	UL File No:	SA-2337
LRA-Half Winding		RPM:	3500	UL File Date:	16-Dec-2004
LRA Low* (Amp):		Max Operating Current	6.7		
RLA, MCC/1.4;use for contactor selection (Amp):		7.3			
RLA, MCC/1.56;use for breaker & wire size selection		6.5			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	60	3	200/230	High Temp
R-134a HFC	50	3	200/220	High Temp
R-404A HFC	60	3	200/230	Extended Medium Temp
R-404A HFC	50	3	200/220	Extended Medium Temp
R-404A HFC	60	3	200/230	Medium Temperature
R-404A HFC	50	3	200/220	Medium Temperature
R-507 HFC	60	3	200/230	Extended Medium Temp
R-507 HFC	50	3	200/220	Extended Medium Temp
R-507 HFC	60	3	200/230	Medium Temperature
R-507 HFC	50	3	200/220	Medium Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-22 HCFC	50	3	200/220	High Temp
R-407C HFC	60	3	200/230	High Temp
R-407C HFC	50	3	200/220	High Temp
R-407A HFC	60	3	200/230	Extended Medium Temp
R-407A HFC	50	3	200/220	Extended Medium Temp
R-448A HFO	50	3	200/220	Medium Temperature
R-448A HFO	60	3	200/230	Medium Temperature
R-448A HFO	50	3	200/220	Extended Medium Temp
R-448A HFO	60	3	200/230	Extended Medium Temp
R-449A HFO	50	3	200/220	Medium Temperature
R-449A HFO	60	3	200/230	Medium Temperature
R-449A HFO	60	3	200/230	Extended Medium Temp
R-449A HFO	50	3	200/220	Extended Medium Temp