

### Rating Conditions

20 °F Superheat  
 0 F Subcooling  
 95 °F Ambient Air Over

60 Hz Operation

### HIGH TEMPERATURE

### ZS26KAE-TF5

HCFC-22

COPELAND SCROLL®

TF5 200/230-3-60

Condensing Temperature °F  
 (Sat. Dew Pt. Pressure, psig) Evaporating Temperature °F (Sat. Dew Pt. Pressure, psig)

	0.0 (24)	5.0 (28)	15.0 (38)	20.0 (43)	30.0 (55)	40.0 (69)	45.0 (76)	55.0 (93)
150.0 (382) C P A M E %					25,700	31,500	34,700	42,100
					4,160	4,410	4,520	4,650
					13.7	14.3	14.6	15.0
					473	568	621	741
					6.2	7.2	7.7	9.1
					67.5	68.1	68.5	69.9
135.0 (317) C P A M E %				23,300	28,900	35,200	38,700	46,900
				3,440	3,650	3,850	3,930	3,990
				11.8	12.3	12.8	13.0	13.3
				397	482	578	632	754
				6.8	7.9	9.2	9.9	11.8
			68.7	69.9	69.9	70.0	71.0	
120.0 (260) C P A M E %			23,300	26,000	31,900	38,800	42,700	51,700
			2,920	2,990	3,160	3,320	3,370	3,380
			10.4	10.6	11.0	11.4	11.6	11.7
			367	407	492	589	644	768
			8.0	8.7	10.1	11.7	12.7	15.3
		70.6	71.7	71.8	70.8	70.4	70.8	
110.0 (226) C P A M E %	17,000	19,550	24,800	27,700	33,900	41,200	45,400	54,900
	2,610	2,580	2,640	2,700	2,860	2,990	3,030	3,000
	9.7	9.6	9.8	9.9	10.3	10.6	10.7	10.7
	261	298	373	412	498	596	652	778
	6.6	7.6	9.4	10.3	11.9	13.8	15.0	18.3
62.4	67.5	72.6	73.2	72.2	70.4	69.6	69.1	
100.0 (196) C P A M E %	18,300	20,900	26,300	29,300	35,900	43,600	48,000	58,000
	2,350	2,330	2,380	2,440	2,580	2,690	2,720	2,650
	9.1	9.0	9.1	9.3	9.6	9.9	9.9	9.8
	268	303	377	416	503	603	659	787
	7.8	9.0	11.1	12.0	13.9	16.2	17.7	21.9
65.2	69.8	73.8	73.8	71.6	68.6	67.3	65.5	
80.0 (144) C P A M E %	20,500	23,200	29,000	32,300	39,500	48,100	53,000	64,200
	1,890	1,870	1,925	1,980	2,100	2,180	2,180	2,070
	8.1	8.0	8.1	8.3	8.5	8.7	8.7	8.4
	275	309	382	422	510	613	671	804
	10.8	12.4	15.1	16.3	18.8	22.1	24.3	31.0
68.1	71.4	72.3	70.6	65.2	58.8	55.6	48.8	
60.0 (102) C P A M E %	22,100	25,000	31,300	34,800				
	1,530	1,525	1,595	1,650				
	7.5	7.4	7.5	7.7				
	275	309	382	422				
	14.5	16.4	19.7	21.1				
64.5	65.7	61.9	57.9					
40.0 (69) C P A M E %	23,100							
	1,310							
	7.3							
	268							
	17.7							
50.2								

C: Capacity (Btu/hr), P: Power (W), A: Current (Amps), M: Mass Flow (lb/hr), E: EER (Btu/Wh), %: Isentropic Efficiency (%)

Nominal Performance Values (±5%) based on 72 hours run-in. Subject to change without notice. Current @ 230 V