RHEEM COMMERCIAL

SOLUTIONS

ELECTRIC LIGHT DUTY WATER HEATERS WITH TERMINAL BLOCK

Identify the appropriate conversion kits for easy field level conversions



Identify the required voltage & heating element wattage.



Choose the gallon capacity required.



See chart to choose the compatible conversion kit.

208V 6/6
is the
Recommended Tank
Stocking Option for
Maximum Flexibility
& Conversions



Rheem Light-Duty Electric with Terminal Block

28 to 119.9-Gallon Capacities 208/240/277/480 Voltages All Wattages Available

RHEEM ELD FIELD CONVERSION CHART																					
VOLTA	208V				240V				277 V				480V								
ELEMENT WATTAGE		3/3	4/4	4.5/4.5	5/5	6/6	3/3	4/4	4.5/4.5	5/5	6/6	3/3	4/4	4.5/4.5	5/5	6/6	3/3	4/4	4.5/4.5	5/5	6/6
CONVERSION KIT MODEL NUMBERS																					
GALLON CAPACITY	30	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	09	61	62
	40	,509	209	500	SP20946	SP2094	209	SP20949	20950	SP2095	2095	2095	2095	209	20956	2095	SP20958	20959	SP20960	5096	SP2096
	50	SP	S	SP	S	R	SP	SF	SP	S	SP	S	S	SP	SP	S	S	SP	S	SP	R
	66	0967	89	6960	170	7	72	73	174	75	921	77	178	62	980	181	182	0983	184	0985	980
	80	N I	209	N 1	SP20970	SP209	209	SP2097	500	500	500	209	209	209	20980	209	20982	209	20984	\sim	SP20986
	120	SP	S	S S	S	R .	S	R	SP	SP	В	SP	S	SP	SP	SP	SP	S	SP	SP	S

ELEMENT	VOLTAGE								
WATTAGE	208	240	277	480					
3,000									
4,000									
4,500		N	on-Fused						
5,000	Fused								
6,000	Fused	Fused							
6,050	Fused	Fused							

Convert FTB (fused terminal block) into any voltage/wattage combination)

NOMINAL GALLON	MODEL NUMBERS							
CAPACITY	NON-FUSED	FUSED						
30	ELD30-TB	ELD30-FTB						
40	ELD40-TB	ELD40-FTB						
50	ELD52-TB	ELD52-FTB						
65	ELD66-TB	ELD66-FTB						
80	ELD80-TB	ELD80-FTB						
119.9	ELD120-TB	ELD120-FTB						
28	ELDS30-TB	ELDS30-FTB						
36	ELDS40-TB	ELDS40-FTB						
47	ELDS52-TB	ELDS52-FTB						

WARRANTY DETAILS:

3-Year Limited Tank, Upgradable to 5-Years and 1-Year Limited Parts Warranty

NOTES:

- All models are shipped in SIM configuration.
- Available in Fused or Non-Fused (Fused if over 48 Amps)
- Recommending Stocking Option = ELD## -FTB
- For greater flexibility order model numbers ending in FTB (Fused Terminal Block)




Terminal Block Conversion Options


- Simultaneous to Non-Simultaneous
- Single Phase to Three Phase
- Heating Element, with Element Kit

FACTORY WIRING 4 WIRE SIMULTANEOUS


Secondary Branch to Electrical Distribution Panel, Off-Peak Meter or




SINGLE PHASE SIMULTANEOUS




SINGLE PHASE NON-SIMULTANEOUS



THREE PHASE SIMULTANEOUS



THREE PHASE NON-SIMULTANEOUS



non-fused, but with a horizontal wiring orientation.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating • 1115 Northmeadow Parkway, Suite 100 Roswell, Georgia 30076 • www.rheem.com

